



# SPECIAL DELIVERY®

## RELIABLE GENTLE HANDLING

The PPM Technologies Special Delivery conveyor gently handles the most delicate of products maintaining quality of fragile, coated or friable food products. With long pan lengths, product drops are removed improving product quality throughout the distribution and packaging line.

The Special Delivery design eliminates leaf springs and base structures reducing installation and maintenance costs. With lengths up to 100' (30.5m), packaging and distribution line layouts are simplified.

## FLEXIBLE OPERATION

With intermediate and end drives, the Special Delivery can easily be designed to suit a variety of layouts. The Special Delivery is ideal for scales and distribution modules and with ceiling mounting support structure is greatly minimized.

The Special Delivery is easily customized to suit the most difficult of application needs requiring gentle handling. Our custom in-line storage solution offers processors a quick storage solution to handle temporary product surges. And, when not used for storage the unit converts to a simple transfer conveyor.

The PPM Technologies Special Delivery conveyor will add value to your packaging and distribution line by delicately handling products from potato chips and snacks to poultry and meats.



### SIMPLE, VERSATILE OPERATION

- Special reversing option to maximize line capability
- Idle mode creating immediate inline storage
- Simple mounting to either ceiling or floor

### GENTLE HANDLING

- Reduce coating loss of product
- Minimize product breakage

### DURABLE, SANITARY DESIGN

- Single conveyors up to 100' long
- Reliable drive design with no gears





## PRIMARY MARKET SEGMENTS

- Confectionery
- Fruits and Vegetables
- Meat, Seafood, and Poultry
- Snacks

## COMMON APPLICATIONS

- Distribution Conveyors
- In-line Storage
- Long Transfer Conveyors
- Scale Feeders



## SPECIFICATIONS

### CONSTRUCTION:

Stainless steel pan

### LENGTH:

8' to 100' long (2.4m to 30.5m)

### WIDTH:

18," 24" and 36" (460mm, 610mm and 915mm)  
Special widths available

### VOLTAGE:

220-240V/60Hz/Three Phase  
380-500V/60Hz/Three Phase  
220-240V/50Hz/Three Phase  
380-500V/50Hz/Three Phase

### OPTIONS:

Covers  
End Gates  
Flared Infeed  
Intermediate Gates  
Lanes  
Proportional Gates

### Americas—PPM Technologies LLC

500 E. Illinois Street | Newberg OR 97132 | USA  
800.246.2034 | 503.538.8575 fax  
info.na@ppmtech.com

### Europe | Middle East | Africa—PPM Technologies LLC

Axis 40 Oxford Road | Stokenchurch  
NR High Wycombe | Buckinghamshire HP14 3SX  
+44 1494 682800 | +44 1494 682801 fax  
Info.eu@ppmtech.com

### Asia—PPM Technologies LLC

3/F Taiseido Bldg | 2-4-7 Hongo  
Bunkyo-ku | Tokyo 113-0033 | JAPAN  
+81 3 5842 3031 | +81 3 5842 3032 fax  
info.asia@ppmtech.com



*The Special Delivery conveyor provides a versatile solution for gentle handling application needs. Units feature a variety of options including: end or intermediate drives, ceiling or floor mounting, intermediate, end and proportional gates.*



*An in-line storage solution featuring horizontal motion technology. This unit features extended sidewalls and plow gate allowing product depth to gently increase when in a temporary idle mode.*



*Horizontal motion drive at rear of conveyor is easily accessible and uses a no gear/no oil design.*